



25 GRAND™

Ultimate Cross Linked Floor Finish

DESCRIPTION:

A revolutionary change in the way you look at floor finishes. 25 GRAND™ maximizes durability without sacrificing gloss. 25 GRAND™ outperforms the competition with greater durability and gloss performance. A hard film with excellent UHS responsiveness to spray buffing or restoring. Application is "Goof Proof" with superior leveling and no mop drag. Builds gloss with fewer coats. Black heel mark resistant.

DIRECTIONS FOR USE:

Before using, read Material Safety Data Sheet for this material.

Floor Preparation:

1. Thoroughly strip floor with any of FORTECH'S floor strippers according to directions.
2. After stripping, make sure floor is clean and residue free.

Application:

1. Using a clean mop bucket lined with a trash can liner to prevent contamination, pour 25 GRAND™ into the mop bucket.
2. Using a clean finish mop, saturate with finish. Place the mop in the wringer and use your weight to press down to remove excess finish.
3. DO NOT WRING OUT
4. Apply finish to the floor in medium coats.
5. Allow each coat to dry a minimum of 20 – 30 minutes.
6. Apply multiple coats until desired gloss is achieved. (3-5 Coats)

Daily Maintenance:

1. Dust mop entire floor surface.
2. Using a clean mop & bucket, mix any of FORTECH'S® neutral pH cleaners and/or disinfectants according to directions.
3. Damp mop floor as needed. No rinsing required.

Restoring:

1. Make sure the floor is completely clean and dry before burnishing. Use FORTECH® RECLAIM™ according to directions.


AVAILABLE PACKAGE SIZES

- FT 31704 4x1 Gallon Bottles
 FT 31705 5 Gallon Pail

TECHNICAL DATA

Form:	Liquid
Color:	Milky White
Specific Gravity @75F:	1.032
pH:	8.4 - 8.8
Nonvolatile Solids:	25% +/-0.3%
Stability:	1 Year Minimum
Density @ 75F:	8.6 lbs Per Gallon
Stability @ 45C:	60 Days Minimum
Slip Resistance:	Meets ASTM D 2047

HMIS Rating



Visit Us Online at
www.formulacorp.com

FORTECH®
PRODUCTS