



25X™

High Solids Floor Finish

DESCRIPTION:

25X™ for the “Finishing Touch” on all types of resilient tile floors, Terrazzo, and sealed wood floors. **25X™** levels smoothly for the ultimate gloss and is highly resistant to black heel marks, scuffing, powdering and water spots. **25X™** retains its high gloss even after detergent damp mopping and scrubbing, yet it is easily sprayed buffed, recoated, repaired, or removed. Can be used with or without a high speed program.

DIRECTIONS FOR USE:

Before using, read Material Safety Data Sheet for this material.

1. Completely strip old finish using **FORTECH® TAKE OFF L.O.™** Low Odor Floor Stripper or **FORTECH® DYNAMITE™** Heavy Duty Floor Stripper.
2. Apply 1 - 2 coats of **FORTECH® SECURE™** Floor Seal if needed, depending on foot traffic.
3. Apply 2 - 4 coats of **25X™** finish.
4. Allow 30 minutes to dry between coats.

Maintaining

- a. Clean - with **FORTECH® NUTRA CLEAN™** daily.
- b. Deep repair - occasionally use **FORTECH® RECLAIM™** to bring new life to the floor.


AVAILABLE PACKAGE SIZES

FT 31304 4x1 Gallon Bottles

TECHNICAL DATA

Form:	Liquid
Color:	Milky White
Specific Gravity @75F:	1.03
pH:	9.0 - 9.4
Nonvolatile Solids:	22% +/-0.3%
Stability:	1 Year Minimum
Density @ 75F:	8.6 lbs Per Gallon
Stability @ 45C:	60 Days Minimum
Slip Resistance:	Meets ASTM D 2047

HMIS Rating



Visit Us Online at
www.formulacorp.com

FORTECH®
PRODUCTS