



# ACCLAIM™

## High Gloss Metal Interlock Floor Finish

### DESCRIPTION:

**ACCLAIM™** for the “Finishing Touch” on all types of resilient tile floors, terrazzo, and sealed wood floors. **ACCLAIM™** levels smoothly for the ultimate gloss and is highly resistant to black heel marks and scuffing. **ACCLAIM™** is slip resistant and meets or exceeds ASTM specifications. **ACCLAIM™** retains its high gloss even after detergent damp mopping and scrubbing, yet it is easily spray buffed, recoated, repaired, or removed.

### DIRECTIONS FOR USE:

*Before using, read Material Safety Data Sheet for this material.*

1. Completely strip old finish using **FORTECH® TAKE OFF L.O.™** Low Odor Floor Stripper or **FORTECH® DYNAMITE™** Heavy Duty Floor Stripper.
2. Apply 1 -2 coats of **FORTECH® SECURE™** Floor Seal if needed depending on foot traffic..
3. Apply 3 - 5 coats of **ACCLAIM™** finish.
4. Allow 30 minutes to dry between coats.

### Maintaining

- a. Clean - with **FORTECH® NUTRA CLEAN™** or **NEUTRAL 64™** daily.
- b. Deep repair - Scrub floor with autoscrubber or swing machine and red pad then use **FORTECH® RECLAIM™** spray buff to bring new life to the floor.
- c. If using a high speed machine use **FORTECH® RECLAIM™** and follow the directions for **RECLAIM™** usage.


### AVAILABLE PACKAGE SIZES

FT 31104	4x1 Gallon Bottles
FT 31105	5 Gallon Pail
FT 31155	55 Gallon Drum

### TECHNICAL DATA

Form:	Liquid
Color:	Milky White
Specific Gravity @75F:	1.02
pH:	9.0 - 9.4
Nonvolatile Solids:	18% +/-0.3%
Stability:	1 Year Minimum
Density @ 75F:	8.5 lbs Per Gallon
Slip Resistance:	Meets ASTM D 2047

### HMIS Rating



Visit Us Online at  
[www.formulacorp.com](http://www.formulacorp.com)

**FORTECH®**  
**PRODUCTS**