



DYNAMITE™

Wax And Finish Stripper

DESCRIPTION:

DYNAMITE™ Wax and Finish Stripper is especially formulated to remove long-term build-up of all water based waxes and synthetic polymer floor finishes including metal interlocked detergent-resistant finishes. **DYNAMITE™** can also be used as an economical and effective industrial cleaner, it penetrates, reacts, and suspends greasy soil and wax in solution for easy rinsing. **DYNAMITE™** may be sprayed, brushed, or mopped on and can also be used in conjunction with pressure sprayers, steam cleaning equipment, and automatic scrubbers. **DYNAMITE™** contains MEA, which in combination with its other solvents and detergent-based ingredients, quickly penetrates, emulsifies and suspends built up wax and finish.

DIRECTIONS FOR USE:

Before using, read Material Safety Data Sheet for this material.

1. Depending on build up dilute stripper from 1:4 TO 1:16 with hot water.
2. Apply diluted stripper generously to small areas. Solution should stand approximately 5-10 minutes. Do not allow to dry.
3. Scrub with floor machine using a stripping pad. Use a scrubbing pad and long handled scraper along edges.
4. Pick up residue using wet vacuum.
5. Immediately flood rinse with clear water and vacuum. Repeat. Scrubbing during the first water rinse is helpful.
6. When dry, check for missed areas and restrip.
7. Apply **FORTECH® SECURE™** Floor Sealer and finish when clean and dry if desired. (NOTE: Autoscrubbers use the double pass system (Scrub/Flood/Scrub/Pick-up).


AVAILABLE PACKAGE SIZES

FT 30104 4x1 Gallon Bottles
 FT 30105 5 Gallon Pail

TECHNICAL DATA

Color:	Red
Odor:	Pleasant
Specific Gravity @ 75F:	1.05
Density @ 75F:	8.7 lbs/Gallon
pH:	13.0
Viscosity @ 75F:	Non-Viscous
Flash Point:	None
Stability:	1 Year Minimum
Freeze/Thaw Stability:	3 Cycles Minimum
pH 1% Solution:	12.2
Solvents:	Glycol Ethers
Phosphates:	None

HMIS Rating



Visit Us Online at
www.formulacorp.com

FORTECH®
PRODUCTS