



NEW HEIGHTS™

Ultra High Gloss Floor Finish

DESCRIPTION:

NEW HEIGHTS™ is formulated to provide the best looking floor in today's ultra high speed burnishing regimens. This product is a proven blend of internally cross linked and thermoplastic polymers and balanced microcrystalline waxes. The resulting film is durable and will withstand high traffic.

- Outstanding black heel and scuff mark resistance.
- Continues to outperform when other finishes fail.
- Responds to burnishing, thus minimizing the need for stripping and recoating.
- Self-sealing, does not require a floor sealer.
- Outstanding leveling for ease of application.
- Low odor

DIRECTIONS FOR USE:

Before using, read Material Safety Data Sheet for this material.

Application:

Using a clean rayon/blend mop, apply thin coats of NEW HEIGHTS™. Allow 15-20 minutes to dry between coats. Four coats are recommended. FORTECH® SECURE™ Floor Sealer can be used for the first two coats.

Maintenance:

Daily: Dust mop. Wet mop with clean mop or autoscrubber (white pad) and NUTRA CLEAN™ for deep cleaning use red pads.

Burnish: 1 to 3 times per week with a white pad and a high speed or ultra high speed burnisher.

Use FORTECH® RECLAIM™ at least once a week for deep repair.

AVAILABLE PACKAGE SIZES


FT 31204 4x1 Gallon Bottles
 FT 31205 5 Gallon Pail

Visit Us Online at
www.formulacorp.com

TECHNICAL DATA

Form:	Liquid
Color:	Milky White
Specific Gravity @75F:	1.03
pH:	8.0 - 9.0
Nonvolatile Solids:	19.0% +/-0.3%
Stability:	1 Year Minimum
Slip Resistance:	Meets ASTM D 2047

HMIS Rating



FORTECH®

PRODUCTS