



# TANK 50/50™

## Tank Cleaning Compound

### DESCRIPTION:

**TANK 50/50™** is a unique product with many uses. **TANK 50/50™** is a 100% active blend of sequesterants, soil suspenders/penetrants and low foam/defoaming surfactants and solvents. **TANK 50/50™** dissolves quickly and completely. Free rinsing formulation prevents hard water and detergent spotting. **The many and varied uses of TANK 50/50™ include:** Mechanical spray parts washing. Use as a non-chlorinated, aluminum safe dishwashing powder. A soak/hot tank solution for ferrous and non-ferrous metals. Pressure wash detergent. A non-caustic CIP circulation cleaner.

### DIRECTIONS FOR USE:

*Before using, read Material Safety Data Sheet for this material.*

**SAFE ON ALUMINUM\* - NO FREE ALKALI  
LOW FOAMING - NON FLAMMABLE**

\*CAUTION: At temp higher than 100°F and immersion times greater than 30 minutes.

The varied uses for **TANK 50/50™** allow for only general guidelines. Experimentation is encouraged.

#### SOAK TANK:

**LIGHT SOIL:** 1/2 lb per 10 gallons of water.  
**MEDIUM SOIL:** 1 lb per 10 gallons of water.  
**HEAVY SOIL:** 1 1/2 lb per 10 gallons of water

#### MECHANICAL SPRAYER:

Dilute to approximately 0.5% in water. For example dilute 1oz in 10 gallons of water.

#### AVAILABLE PACKAGE SIZES


FT 92440 40 Pound Pail

Visit Us Online at  
[www.formulacorp.com](http://www.formulacorp.com)

### TECHNICAL DATA

Form:	Powder
Color:	White
Fragrance:	None
pH 1% Solution:	12.0 - 12.5
Chlorine:	None
Solvents:	None
Alkalinity:	22.5% Na <sub>2</sub> O
Phosphates:	12.2% P
Free Caustic Soda:	-0-
Foam at < 120°F:	Defoam
Foam at > 120°F:	Low

### HMIS Rating



**FORTECH®**  
**PRODUCTS**