

RUST OFF

SPRAY ON - RINSE OFF RUST REMOVER

Description:

RUST-OFF is specifically manufactured for removing rust and oxidation on pipes and metal parts.

Directions for Use:

Before using, read Material Safety Data Sheet for this product.

CAUTION:

WEAR GLOVES AND SAFETY GLASSES.

1. Use a nylon scrub pad to loosen corrosion on surface.
2. Apply **RUST-OFF** generously to rusted area, agitate and let stand for 15 minutes.
3. Rinse treated area with water.
4. Towel dry and coat with penetrating lubricant.

RUST-OFF may also be used on steel wheels, frames and for removing running rust on paint.

Safety:

DANGER: Corrosive - Causes severe eye and skin damage.

Contains Phosphoric Acid, Hydrochloric Acid and 2-Butoxyethanol. Fatal or harmful if swallowed. Do not breathe vapors or fumes. Produces chemical burns. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid contamination of food. Remove and wash contaminated clothing.


FIRST AID:

Skin: Flush with water immediately then cover with moist magnesia or baking soda. **Eyes:** Flush with water for at least 15 minutes. Call a physician. **If Swallowed:** Do NOT induce vomiting. Drink milk, egg whites, gelatin solution, or large quantities of water. Call a physician.

TECHNICAL DATA

Form: Liquid
Color: Water White
Acid Content: 40% Phosphoric
Acid Content: 5% Hydrochloric
Viscosity: Thin
pH: >2%
Foam: Low
Solvents: 2-Butoxyethanol
Specific Gravity: 1.27
Density: 10.5

Formula
Corp



4432 C Street NE • Auburn, WA 98002
(800) 772-7005 • Fax: (253) 880-0185